



Range of Cooling Water Chemicals.

Product Code: CFAU-505

DESCRIPTION:

CFAU-505 is a low molecular weight copolymer that acts as an excellent deposit control agent and dispersant for cooling towers, especially those with highly turbid water or fly ash intake. It has exceptional thermal and hydrolytic stability. As a powerful dispersant, CFAU-505 prevents different forms of sludge from precipitating in cooling water conditions, maintains higher levels of hardness, and minimizes blowdown. It also prevents deposit accumulation in low-velocity areas and can gradually remove existing scales at slightly higher doses.

Complete filtration and utility breakthrough technologies for industrial water treatment are designed to work effectively and protect a wide range of cooling, heating, cleaning, and filtration systems.

PRODUCT BENEFITS:

- High performance, multi-functional formulation.
- Protect industrial cooling systems from scale, corrosion and fouling.
- Improves system protection.
- More cost effective product control.
- Excellent corrosion control.
- Excellent scale control.
- Dispersants for iron, suspended solids, dust and silt.
- Economical – can be used at low dosage rates.



APPLICATION

Towers, Air Washers, Evaporative Condensers, Ship Condensers, water Heat Exchangers, Radiators, Gear Injection Molding Machines, Blow Molding Machines, Housings, D.G.Sets etc.

HANDLING AND PRECAUTIONS

CFAU-505 range of chemicals can irritate eyes and skin. Avoid contact with eyes, skin, or clothing. Handle this product with care, as with all chemicals.

PACKAGING

50,35,20 Kg carboy packing

NB: Other detail, technical specifications, doses and data sheet of the chemical can be communicated on demand. Please email us your enquiry.
